

# Duette® with LiteRise®

## EASE, SAFETY AND BEAUTY

The LiteRise® cordless lifting system offers your customers remarkable ease of operation, along with the added benefit of enhanced child and pet safety. And now, Duette® with LiteRise shades come standard with a fabric-covered valance integral with the headrail. This gives the shades an inviting, soft look at the top to enhance their overall appearance.

### Why should you recommend the LiteRise lifting system to your customers?

- Ease and convenience of shade operation at the touch of finger
- Improved aesthetics and enhanced safety with no operating cords
- Fabric-covered valance provides a soft look at the top of the shade and precise color coordination to the shade's fabric
- New headrail design features installation brackets with minimum inside mounting depth of only 1/2" for all pleat sizes

### Information to remember when selling Duette with LiteRise shades:

- Available in sizes up to 120" x 84"
- Offered in all pleat sizes and most fabrics
- Available in Standard, Top-Down/Bottom-Up and Duolite™ design options
- Lifetime Limited Warranty



*Now Duette with LiteRise shades feature a standard fabric-covered valance integral to the headrail for a soft look at the top and precise color coordination to the fabric. The LiteRise cordless system offers ease of operation, as well as enhanced child and pet safety.*

# HunterDouglas

dealers.hunterdouglas.com

# Duette<sup>®</sup> with LiteRise<sup>®</sup>

## APPLICATIONS

- Standard
- Top-Down/Bottom-Up
- Duolite™
- Fabric-covered valance standard

## SIZE STANDARDS

### Standard

- Minimum ordered width: 18"
- Maximum ordered width: 120"
- Maximum ordered width, end mount\*: 48"
- Minimum ordered height: 6"
- Maximum ordered height: 84"

### Top-Down/Bottom-Up

- Minimum ordered width: 20"
- Maximum ordered width: 120"
- Maximum ordered width, end mount\*: 48"
- Minimum ordered height: 6"
- Maximum ordered height: 84"

### Duolite

- Minimum ordered width: 20"
- Maximum ordered width: 72"
- Maximum ordered width, end mount\*: 48"
- Minimum ordered height: 6"
- Maximum ordered height: 84"

\*End mount not available with 1¼" pleat.

## MOUNTING REQUIREMENTS

### ¾" Pleat

#### Inside (IB) and End (EB) Mount

- Minimum mounting depth: ½"
- Minimum mounting depth, flush mount: 2¼"
- Minimum mounting depth, end mount: 1¼"

#### Outside (OB) Mount

- Minimum flat vertical surface: ⅝"

### ¾" Pleat and Double Honeycomb

#### Inside (IB) and End (EB) Mount

- Minimum mounting depth: ½"
- Minimum mounting depth, flush mount: 2⅞"
- Minimum mounting depth, end mount: 1¼"

#### Outside (OB) Mount

- Minimum flat vertical surface: ⅝"

### 1¼" Pleat

#### Inside (IB) Mount

- Minimum mounting depth: ½"
- Minimum mounting depth, flush mount: 3⅝"

#### Outside (OB) Mount

- Minimum flat vertical surface: 1¼"

## FINISHED DIMENSIONS

### Standard

#### Inside (IB) and End (EB) Mount

- Headrail unit width: -⅜"
- Fabric width: -⅜"
- Shade height: ordered height

#### Outside (OB) Mount

- Headrail unit width: ordered width
- Fabric width: -⅝"
- Shade height: ordered height

### Top-Down/Bottom-Up and Duolite

#### Inside (IB) and End (EB) Mount

- Headrail unit width: -⅜"
- Fabric width: -⅜"
- Shade height: ordered height

#### Outside (OB) Mount

- Headrail unit width: ordered width
- Fabric width: -⅜"
- Shade height: ordered height

## MEASURING PROCEDURES

Round all measurements down to the nearest 1/8".

### Inside (IB) Mount

- Measure the width at the top, middle and bottom of the window opening. Order the smallest measurement.
- Measure the height at the left, center and right of the window opening. Order the largest measurement.
- Measure the diagonals. If the measurements differ by more than ½", an outside mount is recommended.
- Be sure the window opening is deep enough to install the mounting bracket.

### Outside (OB) Mount

- Measure the desired width, allowing at least a 2" overlap on each side of the window opening.
- Measure the desired height. Take into account where the mounting brackets will be attached, and allow a recommended 2" overlap on the bottom, unless the shade hangs to a protruding sill.
- No deductions will be taken; shade is made to exact ordered dimensions.
- Spacer blocks or extension brackets can be used to gain clearance, if necessary.

## ORDERING NOTES

Specify the following information on the order form for each blind:

- Width and height measurements
- Number and name of fabric(s) and color(s)
- Mounting style — inside (IB) mount, end (EB) mount or outside (OB) mount
- Extension brackets for end mount installations
- Extension pole, if desired
- Spacer blocks or extension brackets, if required for added clearance

### Duolite Only

- On order form, list top fabric panel first and bottom fabric panel second
- Both panels must be same pleat size
- Top panel must be sheer, semi-sheer or semi-opaque; bottom panel must be semi-opaque or opaque

## CLEANING OPTIONS

- See the installation & care instructions supplied with shade for more detailed cleaning procedures.
- Dust with feather duster or low suction hand-held vacuum.
- Spot-clean using a clean cloth and mild detergent solution; blot the fabric gently, do not rub.
- For more thorough cleaning, shade may be immersed in a bathtub filled with mild detergent solution; do *not* immerse headrail; do *not* immerse Eclipse™ opaque fabric.
- Professionally clean using an ultrasonic or injection/extraction cleaning service; Eclipse opaque fabric excluded.

## LIFETIME LIMITED WARRANTY

- Duette honeycomb shades are backed by the Hunter Douglas Lifetime Limited Warranty.

# HunterDouglas

dealers.hunterdouglas.com

© 2007 Hunter Douglas Inc. ® Registered trademark of Hunter Douglas Inc.  
™ Trademark of Hunter Douglas Inc. Patented in the U.S. and foreign countries.  
Other U.S. and foreign patents pending. 5109350000 6/07

